


## Sphinx Roof 6<sup>®</sup> PAT


CONTACT :  
 GANTAN BEAUTY INDUSTRY CO., LTD.  
 International Business Department  
 E-mail : overseas@gantan.co.jp  
 Phone : +81-466-43-2187 / Fax : +81-466-45-3037  
 URL : http://www.gantan.co.jp/english/index.html




Public facility

### Profile

Unit: mm



### Details (Gantan yuko system)



### Performance

Wind pressure resistance:  
 3000Pa [3kN/m<sup>2</sup>]

\* Value tested by the Japan Testing Center for Construction Materials (steel plate thickness 0.4mm, Roof purlin pitch 606mm, standard hanger specification)

Thermal insulation performance:  
 (heat transmission coefficient)  
 0.330W/(m<sup>2</sup>·K) [0.284kcal/(m<sup>2</sup> h°C)]

\* Gantan Yuko System, steel frame specification, mesh specification

### Standard Materials Thickness

Material	Thickness
Pre-painted aluminum, fluoro-resin coated aluminum	0.7mm
Copper and patinaed copper	0.4mm
Pre-painted stainless steel, fluoro-resin coated stainless steel	0.45mm
Fluoro-resin galvalume steel	0.45mm
Pre-painted galvalume steel, Painted steel	0.4mm

### Specifications

- Effective width: 395mm
- Effective length: 11m or longer made on site
- Slopes of 3/100 or steeper
- Radius of Curvature: 7meters or more