

Gantan Spring Roof-800[®] PAT


CONTACT :
 GANTAN BEAUTY INDUSTRY CO., LTD.
 International Business Department
 E-mail : overseas@gantan.co.jp
 Phone : +81-466-43-2187 / Fax : +81-466-45-3037
 URL : http://www.gantan.co.jp/english/index.html

Japan's top manufacturer of lateral roofing ※1




school


■ Profile Unit: mm



■ Details (Gantan yuko system)



■ Features of the spring-back seam



■ Performance

Wind pressure resistance:
 8000Pa [8.0kN/m²]

* Value tested by the Japan Testing Center for Construction Materials (steel plate thickness 0.4mm, rafter spacing 490mm, standard hanger specification)

Thermal insulation performance:
 (heat transmission coefficient)
 0.261W/(m²·K) [0.224kcal/(m² h°C)]

* Gantan Yuko System, steel frame specification, mesh specification

■ Standard Materials Thickness

Material	Thickness
Painted aluminum, fluoro-resin coated aluminum	0.7mm
Copper and patinaed copper	0.4mm
Painted stainless steel, fluoro-resin coated stainless steel	0.45mm
Fluoro-resin galvalume steel	0.45mm
Painted galvalume steel, Painted steel	0.4mm

■ Specifications

- Effective width:240mm
- Effective length:4200 mm (3640 mm for copper sheet)
- For slopes of 25/100 or steeper